



Excelsys Technologies Ltd.  
27 Eastgate Drive  
Eastgate Business Park  
Little Island  
Co. Cork, Ireland

Tel: + 353 21 4354716  
Fax: + 353 21 4354864

## DECLARATION OF CONFORMITY

**Product Name** : UltiMod Series

**Product Type** : Component Power Supply

Model Numbering System

UX6 abcdef g kh j for the 6Slot UltiMod powerPac units populated with powerMod Modules, and  
UX4 abcd g kh j for the 4Slot UltiMod powerPac units populated with powerMod Modules,

where:

"a" = 0, 1, 2, 3, 4, 5, 6, 7, 8, A, B, C, D, E, F, G, H, J, K, L

"b" = 0, 1, 2, 3, 4, 5, 6, 7, 8, A, B, C, D, E, F, G, H, J, K, L

"c" = 0, 1, 2, 3, 4, 5, 6, 7, 8, A, B, C, D, E, F, G, H, J, K, L

"d" = 0, 1, 2, 3, 4, 5, 6, 7, 8, A, B, C, D, E, F, G, H, J, K, L

"e" = 0, 1, 2, 3, 4, 5, 6, 7, 8, A, B, C, D, E, F, G, H, J, K, L

"f" = 0, 1, 2, 3, 4, 5, 6, 7, 8, A, B, C, D, E, F, G, H, J, K, L 8

"g" = '-', P, C, R or S

'-' = Standard model (nominal voltage)

P = Specific voltage adjustment settings

C = Conformal coating

R = Ruggedized for vibration

S = C + R

"k" = any alphanumeric character describing customer internal wiring lengths. Where no internal wiring exists and standard IEC appliance inlet is used k=0.

"h" = 0, 2, 4, 6

0 = Standard model

2 = Reverse Fan

4 = Low Leakage

6 = 2 + 4

"j" = any alphanumeric character..

Excelsys Technologies Ltd. confirms that this product conforms to:

### Safety

Safety of Medical Electrical Equipment: IEC 60601-1(ed.3)

Tested and found to be in conformity to IEC60601-1(ed.3)

Safety of Medical Electrical Equipment: IEC 60601-1 2006

Tested and found to be in conformity to IEC60601-1 2006

### Supplementary Information

Safety tests were conducted by UL. By conformance with the standards referenced, the product follows the provisions of EC Directive 2006/95/EC (L.V.D. Directive) with the exception of the enclosure requirement. These products are only for inclusion by professional installers within other equipment and must not be operated as stand alone products.

These power supplies provide REINFORCED INSULATION between input and output and may be used as an SELV circuit or a TNV power source which is insulated from the AC mains.

The maximum ambient temperature must not exceed 40°C at full load.

Place of Issue: Cork, Ireland  
Date of Issue: 24th April 2014

For and on behalf of  
Excelsys Technologies Limited

Dermot Flynn